



TYPICAL PROPERTIES

Kinematic Viscosity, @ 100°C	12.3 cSt
Kinematic Viscosity, @ 40°C	73.7 cSt
Viscosity Index	166
Cold Crank Simulator, @ -30°C	6,230cP
Pour Point	-42°C
Flash Point, COC	220°C
Total Base Number (TBN)	7.7 mgKOH.g ⁻¹
Density, @ 15°C	0.853 g/cm ³

Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

HyperDrive KXR

5W-30 C3 Fully Synthetic Engine Oil (Mid SAPS)

CODE: KXEER40

HyperDrive KXR 5W-30 C3 is a fully synthetic mid SAPS engine oil produced from high-quality synthetic base oils and top-tier performance additives for use in petrol and diesel engines, including hybrid engines, requiring an SAE 5W-30 oil meeting the specifications listed below.

FEATURES / BENEFITS

- Mid SAPS technology for use in petrol or diesel engines with or without exhaust after treatment devices.
- Top-tier performance additives deliver high levels of engine cleanliness and reduced wear
- High-quality synthetic base oils ensure long oil life and extended oil drain interval
- Low viscosity oil improves engine efficiency, reducing running costs and emissions
- Provides optimum performance and engine protection at operating temperature

PERFORMANCE SPECIFICATIONS

HyperDrive KXR 5W-30 C3 meets the requirement of:

- ACEA: C3
- API: SN/CF
- BMW: Longlife-04
- GM: Dexos 2
- MB: 229.31

AVAILABILITY



Hyperdrive, 47 Heming Road, Redditch, B98 0EA
Tel: 0800 371 910 hyperdrivelubricants.com