



TYPICAL PROPERTIES

Kinematic Viscosity, @ 100°C	11.3 cSt
Kinematic Viscosity, @ 40°C	96.2 cSt
Viscosity Index	103
Brugger Test	21 N/mm ²
Four Ball Wear Scar, 1h 30kg	0.83 mm
Pour Point	-27°C
Flash Point, COC	230°C
Density, @ 15°C	0.874 g/cm ³

Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

HyperDrive KX+

Chain Oil 100

CODE: KXENA10

HyperDrive KX+ Chain Oil 100 is a high-quality mineral oil based chain oil suitable for use to lubricate chainsaw bars and cutting chains where either an ISO 100 or SAE 30 viscosity oil is required. Formulated to reduce oil "fling", maintaining lubrication and ensuring smooth continuous chain motion. The high viscosity formulation reduces wear, extending the life of the chainsaw and minimises lubricant losses

FEATURES / BENEFITS

- Lubricates cutting chains and chainsaw bars, reducing friction and promoting continuous smooth chain motion
- High viscosity formulation reduces wear and protects chainsaw bars and cutting chains
- Carefully selected additives contribute significant tackiness, preventing 'fling off' minimising lubricant loss and maintaining lubrication
- Mineral oil based, protects against rust and corrosion

AVAILABILITY



Hyperdrive, 47 Heming Road, Redditch, B98 0EA
Tel: 0800 371 910 hyperdrivelubricants.com