



## TYPICAL PROPERTIES

Kinematic Viscosity, @ 100°C	11.6 cSt
Kinematic Viscosity, @ 40°C	69.0 cSt
Viscosity Index	163
Cold Crank Simulator, @ -35°C	6,030 cP
Pour Point	-42°C
Flash Point, COC	>200°C
Density, @ 15°C	0.853 g/cm³

Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.  
**Version Date:** 11/02/2025

## HyperDrive KXR

# 5W-30 C3 RN

**CODE:** KXEEH41

HyperDrive KXR 5W-30 C3 RN is a high performance fully synthetic mid SAPS long life engine oil, designed for use in passenger car petrol and diesel engines, including direct injection engines, fitted with exhaust after treatment systems which require an ACEA C3 5W-30 oil meeting the specifications below. Expertly formulated to ensure adequate film thickness at operating temperatures, to protect against wear and corrosion. The low viscosity oil reduces internal friction to improve engine efficiency and reduce emissions. Top tier additives ensure the oil protects throughout the recommended oil drain interval whilst still protecting exhaust after treatment systems.

## FEATURES / BENEFITS

- Fully synthetic low viscosity engine oil designed to protect engines from wear, and corrosion, even in the presence of soot, whilst reducing internal friction, increasing engine efficiency and reducing fuel consumption and environmental emissions
- Mid SAPS formulation protects exhaust after treatment systems, such as particulate filters and three-way catalysts (TWC), further reducing environmental emissions
- High quality base oils and top tier additives ensure that the oil is shear stable and remains within grade for the oil ensuring adequate protection of the engine throughout the recommended oil drain interval
- Excellent oxidation stability protects the oil throughout extended oil drain intervals, reducing the build-up of sludges and deposits within the oil and the engine, maintaining engine condition and performance
- Suitable for use in high performance passenger car petrol and diesel engines, including turbocharged direct injection (TGDl) engines, fitted with exhaust after treatment systems which require an ACEA C3 5W-30 oil, and for Renault engines requiring RN17 performance, backwards compatible where RN0700 or RN0710 are required

## PERFORMANCE SPECIFICATIONS

HyperDrive KXR 5W-30 C3 RN meets the requirement of:

- ACEA: C3
- RN: RN17

## AVAILABILITY



Certas Energy UK Ltd., T/A Certas Lubricants Solutions. 1st Floor, Allday House, Warrington Road, Birchwood, Warrington, Cheshire, WA3 6GR.  
**Tel:** 0800 371 910 [hyperdrivelubricants.com](http://hyperdrivelubricants.com)

**To order call: +44 800 371 910**

[hyperdrivelubricants.com](http://hyperdrivelubricants.com)