

HYPERDRAVE



TYPICAL PROPERTIES

Appearance	Red Fluid
Kinematic Viscosity, @ 100°C	7.5 cSt
Kinematic Viscosity, @ 40°C	39.8 cSt
Viscosity Index	150
Pour Point	-48°C
Flash Point, COC	>210°C
Density, @ 15°C	0.855 g/cm³

ATF Dexron II

CODE: KXEMS10

HyperDrive KX ATF Dexron II is an automatic transmission fluid, suitable for use where General Motors Dexron IIE, or older, performance is required. Blended using high quality base oils and a balanced additive package, it provides excellent protection against wear, rust and corrosion across a wide temperature range, whilst ensuring the correct friction characteristics to ensure smooth operation of transmission systems.

FEATURES / BENEFITS

- Balanced formulation provides excellent anti-wear performance and corrosion protection
- Good low temperature performance protects even from cold start
- Low friction properties ensure smooth gear shifting and efficient power transfer
- High quality base oils ensure oxidation and thermal stability, maintaining transmission system cleanliness and performance
- Designed to give good foam control maintaining lubricating oil film between moving surfaces

PERFORMANCE SPECIFICATIONS

HyperDrive KX ATF Dexron II is suitable for use where the following specifications are required:

- FORD: Mercon GM: Dexron IIE MAZDA: ATF D-II MB: 236.7
- TOYOTA: ATF D-II

AVAILABILITY









Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

Version Date: 11/02/2025

Tel: 0800 371 910 hyperdrivelubricants.com

Certas Energy UK Ltd., T/A Certas Lubricants Solutions. 1st Floor, Allday House,

Warrington Road, Birchwood, Warrington, Cheshire, WA3 6GR.