



## TYPICAL PROPERTIES

Kinematic Viscosity, @ 100°C	14.4 cSt
Kinematic Viscosity, @ 40°C	85.8 cSt
Viscosity Index	175
Cold Crank Simulator, @ -30°C	5,830 cP
Pour Point	-42°C
Flash Point, COC	>230°C
Density, @ 15°C	0.854 g/cm³

Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.  
Version Date: 18/02/2025

## HyperDrive KXR

### 5W-40 A3/B4

CODE: KXEEC42

HyperDrive KXR 5W-40 A3/B4 is a full SAPS fully-synthetic engine oil for use in naturally aspirated or turbocharged petrol and diesel engines without exhaust emission control systems. High quality base oils, combined with shear stable additives, provide protection from wear, rust and corrosion across a wide range of operating temperatures, and reduce the formation of harmful deposits and sludges, maintaining engine condition and performance.

## FEATURES / BENEFITS

- Fully synthetic formulation protects against oxidation, reducing sludge and deposit formation, maintaining engine condition and performance
- Full SAPS formulation protects naturally aspirated and turbocharged petrol and diesel engines from wear, rust and corrosion, extending engine life
- Shear stable stay in grade formulation maintains viscosity across a wide range of temperatures, providing year round protection
- Low volatility formulation reduces oil consumption and maintains viscosity, ensuring suitable lubrication throughout the oil drain interval

## PERFORMANCE SPECIFICATIONS

HyperDrive KXR 5W-40 A3/B4 meets the requirements of:

- ACEA: A3/B4 • API: SN/CF • MB: 229.5 • MB: 229.3 • MB: 226.5
- PORSCHE: A40 • RENAULT: RN 0700 / 0710 • VW: 502 00/ 505 00

HyperDrive KXR 5W-40 A3/B4 is suitable for use where the following specifications are required:

- ACEA: A3/B3 • MB 229.1

## AVAILABILITY



Certas Energy UK Ltd., T/A Certas Lubricants Solutions. 1st Floor, Allday House, Warrington Road, Birchwood, Warrington, Cheshire, WA3 6GR.  
Tel: 0800 371 910 [hyperdrivelubricants.com](http://hyperdrivelubricants.com)